

N62293

Hughes 269A
(TH-55A)

S/N 880939
(67-16852)

MFG	NEXT	TYPE	NEXT	HOBBS	AFTT
1968	INSP	INSP	ANNUAL	113.9	13110.9
	138.9	25HR	6/09		

PART NAME	PART NUMBER	PART S/N	PART LIMIT	PART HRS@ INST	A/F HRS@ INST	PART TSN	PART TSO	TIME REMAIN	PERCENT REMAIN
M/R BLADE	269A1190-1	S0093	5500 HRS	0.0	13069.2	41.7		5458.3	99.24%
M/R BLADE	269A1190-1	253	5500 HRS	5086.8	13069.2	5128.5		371.5	6.75%
M/R BLADE	269A1190-1	601	5500 HRS	2438.9	13069.2	2480.6		3019.4	54.90%
PITCH BRG SHAFT	269A1240		O/C						
PITCH BRG SHAFT	269A1240		O/C						
PITCH BRG SHAFT	269A1240		O/C						
LL DAMPER	269A1290-1	1850	6000 HRS	0.0	10373.0	2737.9		3262.1	54.37%
LL DAMPER	269A1290-1	1876	6000 HRS	0.0	10373.0	2737.9		3262.1	54.37%
LL DAMPER	269A1290-1	1929	6000 HRS	0.0	10373.0	2737.9		3262.1	54.37%
M/R MAST	269A2020-7		O/C						
M/R DRIVESHAFT & HUB	269A5305-3	5402M2	3000 HRS	0.0	10959.0	2151.9		848.1	28.27%
SUPPORT STRUT	269A2015-11		O/C						
SUPPORT STRUT	269A2015-11		O/C						
TAIL BOOM	269A2320	29-1102	17370 HRS	0.0	0.0	13110.9		4259.1	24.52%
STAB. HOR.	K2516	1170342	4200 HRS	0.0	12997.0	113.9		4086.1	97.29%
XMSN RING GEAR	269A5193		6000 HRS	4361.0	12990.0	4481.9		1518.1	25.30%
XMSN PINION	269A5103	20	6000 HRS	2982.0	12395.0	3697.9		2302.1	38.37%
XMSN CARRIER	269A5194	ASO 510	6000 HRS	4361.0	12990.0	4481.9		1518.1	25.30%
L P COUP. SHAFT	269A5559	3497	6000 HRS	0.0	7970.0	5140.9		859.1	14.32%
T/R BLADE *	269A6035-17	5633	5000 HRS	3217.0	12453.0	3874.9		1125.1	22.50%
T/R BLADE *	269A6035-17	5461	5000 HRS	3217.0	12453.0	3874.9		1125.1	22.50%
T/R STRAP	269A6065-507	S-1642	1531 HRS	0.0	12997.0	113.9		1417.1	92.56%
T/R SHAFT	269A6040-5	3517	3000 HRS	0.0	10558.0	2552.9		447.1	14.90%
M/R BEARING *	269A5050-73	A1451	3000 HRS	0.0	10959.0	2151.9		848.1	28.27%
PINION BEARING	269A5051-20	N/A	3000 HRS	0.0	12395.0	715.9		2284.1	76.14%
IDLER BRG (2)	269A5050-74	N/A	3000 HRS	0.0	11759.0	1351.9		1648.1	54.94%
UPR. PULLEY BRG (2)	269A5050-56	N/A	600 HRS	0.0	12997.0	113.9		486.1	81.02%
LWR. PULLEY BRG (2)	269A5050-57	N/A	1800 HRS	0.0	12602.0	508.9		1291.1	71.73%
T/R G/B BRG (4)	369A5420-1,2,3		3000 HRS	0.0	10161.0	2949.9		50.1	1.67%

OVERHAUL ITEMS

ENGINE	HIO-360-B1A	L-4812-51A	1500 O/H	0.0	13027.0	13110.9	83.9	1416.1	94.41%
MAIN XMSN	269A5175-9	36-0862W	3000 MO/H	0.0	12395.0		715.9	2284.1	76.14%
MAIN XMSN	269A5175-9	36-0862W	4800 O/H	3766.0	12395.0		4481.9	318.1	6.63%
T/R GEARBOX	369A5400	1171255	2400 O/H	101.2	10160.0	6520.9	3052.1	-652.1	-27.17%

INSPECTION ITEMS

XMSN PINION	269A5103-9		1500 INS	0.0	12395.0		715.9	784.1	52.27%
SWSHPLT BRG*	269A1301		1200 INS	0.0	13110.9		0.0	1200.0	100.00%
M/R BEARING *	269A5050-63		600 INS	0.0	13110.9		0.0	600.0	100.00%
T/R BLADE*	269A6035-		600 INS	0.0	13110.9		0.0	600.0	100.00%
T/R BLADE*	269A6035-		600 INS	0.0	13110.9		0.0	600.0	100.00%
BLTDRV BRG RPCK *	269A5050-78/80		300 INS	0.0	13110.9		0.0	300.0	100.00%

* ITEMS MARKED WITH AN ASTERISK HAVE AN ALTERNATE OR DATED LIFE ALSO

	REF			HOBBS
TRANSPONDER		24 MONTH DUE		OIL CHNG
SWSHPLT BRG RPCK*		24 MONTH DUE	6/10	50 HR INS
BLTDRV BRG RPCK*		24 MONTH DUE	6/10	OIL CHNG
M/R BEARING *		24 MONTH DUE	6/10	100 HR INS
T/R BLADE INS*		12 MONTH DUE	6/09	